



TOWERLINE TL 725

- for indoor applications -

Your Advantages: Security, Flexibility and future-oriented Economy

Security

- Resistant sheet metal cabinet with lockable, illuminated advertising frame and standard poster Caroline

Flexibility

- Easy commutability of components through modular construction type
- Individually adjustable filling heights for optimal adaptation to different requirements
- The TL 725 offers a capacity of around 650 packs and a variety up to 25 different brands

Future-oriented Economy

- State-of-the-art innovative technology
- Different technologies available for realisation of youth protection as an option

Extensive Equipment

- Electronic coin validator – NRI with thread sensors
- Standard lock DOM
- Integrated Flash for software uploads
- Two additional advertising panels for operator information
- Optional convenience equipment: banknote acceptor and coin change giver
- Optional youth protection solution like a remote control





TOWERLINE TL 725

- for indoor applications -



Technical Specifications

all technical data subject to corrections

width 900 mm
 height with socket 1400 mm
 height w/o socket 1140 mm
 depth 480 mm

weight approx. 146 kg
 options resp. 25-30
 amount of columns up to 650 packs
 filling capacity up to 650 packs

Number of implemented ejectors : 25

								3		3
							11	12	13	12
							21	22		22
							11	12	13	14
							BIG			BIG
1	1	1	1	1	1	1	2	1	2	
01	02	03	04	05	06	07	08	09	10	
11	12	13	14	15	16	17	18	19	20	
01	02	03	04	05	06	07	08	09	10	
							BIG			BIG

3		3		3						
23		24		25						
33		34		35						
25		26	27	28	29	30	31	32	33	
BIG		BIG								
2	1	2	1	2	1	1	1	1	1	
13	14	15	16	17	18	19	20	21	22	
23	24	25	26	27	28	29	30	31	32	
15	16	17	18	19	20	21	22	23	24	
BIG		BIG								

Filling capacity

15	x	34	=	510 packs
5	x	11	=	55 packs
5	x	20	=	100 packs
Total =				665 packs

Column height

1	=	810 mm
2	=	280 mm
3	=	470 mm

- = Implemented ejector max. 60 mm packs (pack height: 24 mm)
- = Possible positions for further ejectors
- = Big Packs max. 66 mm packs